



# MultiRAE Benzene

## Wireless Portable Six-Gas Monitor With Benzene-Specific Measurement

The MultiRAE Benzene is the only gas monitor that includes up to 6-gas<sup>1</sup> detection and real-time wireless capability, plus benzene-specific measurement.

The MultiRAE Benzene monitor combines the ability to make quick benzene-specific assessment (“snapshot”) measurements<sup>2</sup> with the advantages of a versatile multi-gas monitor that can support approximately 20 interchangeable sensor options.

Its optional wireless capability improves safety by providing real-time access to instrument readings and alarm status from any location, which delivers better situational awareness and faster incident response.

The MultiRAE Benzene monitor’s unique features make it an ideal instrument for industrial applications, from confined space entry pre-screening to personal protection, leak detection and refinery downstream monitoring.



Multi RAE Benzene used for leak detection

### APPLICATIONS

- Confined space entry pre-screening
- Plant Shutdown (downstream)
- Personal Protection
- Leak detection

- Unique instrument for multiple applications
- Highly versatile and customizable
- Benzene-specific measurement up to 200 ppm with 0.1 ppm resolution
- Man Down Alarm with real-time remote wireless notification
- Fully automatic bump testing and calibration with Auto RAE 2

## FEATURES & BENEFITS

- Versatile multi-gas and Benzene-specific<sup>2</sup> modes
- Wireless access to real-time instrument readings and alarm status from any location<sup>3</sup>
- Unmistakable five-way local and remote wireless notification of alarm conditions, including Man Down Alarm<sup>3</sup>
- Intelligent sensors store calibration data, so they can be swapped in the field<sup>4</sup>
- Continuous data logging (up to 6 months for 5 sensors) and snapshot datalogging capabilities

# MultiRAE Benzene Specifications

INSTRUMENT SPECIFICATIONS	
SIZE	7.6" H x 3.8" W x 2.6" D (193 x 96.5 x 66 mm) without RAE SepTube Cartridge
WEIGHT	3.1oz (880g) without RAE SepTube Cartridge
SENSORS	More than 20 intelligent interchangeable field-replaceable sensors, including PID sensor for VOCs, electrochemical sensors for toxic gases, and oxygen and LEL sensor
BATTERY OPTIONS, RUNTIMES AND RECHARGE TIME	- Rechargeable Li-ion (~12-hr. runtime, < 6-hr. recharge time) - Extended-duration Li-ion (~18-hr. runtime, < 9-hr. recharge time) - Alkaline adapter with 4 x AA batteries (~6-hr. runtime)
DISPLAY	Monochrome graphical LCD display (128 x 160) with backlighting, Automatic screen "flip" feature.
DISPLAY READOUT	- Real-time reading of gas concentrations; non-specific PID measurement ; Man Down Alarm on/off; visual compliance indicator; battery status; datalogging on/off; wireless on/off and reception quality. - STEL, TWA, peak, and minimum values - Benzene-specific snapshot measurement <sup>2</sup>
KEYPAD BUTTONS	3 operation and programming keys (Mode, Y+, and N/-)
SAMPLING	Built-in pump. Average flow rate: 250 cc/min. Auto shutoff in low-flow conditions
CALIBRATION	Automatic with AutoRAE 2 Test and Calibration System or manual
ALARMS	- Wireless remote alarm notification; audible (95 dB @ 30 cm), vibration, visible (flashing bright red LEDs), and on-screen indication of alarm conditions - Man Down Alarm with pre-alarm and real-time remote wireless notification <sup>3</sup>
DATALOGGING	Continuous datalogging (6 months for 5 sensors at 1-minute intervals) - User-configurable datalogging intervals (from 1 to 3,600 seconds) - Snapshot datalogging
COMMUNICATION AND DATA DOWNLOAD	- Data download, instrument set-up and upgrades on PC via desktop charging and PC communications cradle, travel charger, or AutoRAE 2 Automatic Test and Calibration System. - Wireless data and alarm status transmission via built-in RF modem (optional)
WIRELESS NETWORK	ProRAE Guardian Real-Time Wireless Safety System or EchoView Host-based Closed-Loop System
WIRELESS RANGE (TYPICAL)	MultiRAE to RAE Link3 [Z1] Mesh modem ~330 feet (100 meters) MultiRAE to EchoView Host, RAEMesh Reader or RAEPoint ~660 feet (200 meters) MultiRAE to Wi-Fi Access Point ~330 feet (100 meters)
OPERATING TEMPERATURE	-4° to 122° F (-20° to 50° C)
HUMIDITY	0% to 95% relative humidity (non-condensing)
DUST AND WATER RESISTANCE	IP-65 ingress protection rating
HAZARDOUS LOCATION APPROVALS	CSA: Class I, Division 1, Groups A, B, C and D, T4 Class II, Division 1; Groups E, F, G; T85°C ATEX: II 1G Ex ia IIC T4 Ga II 2G Ex ia d IIC T4 Gb with IR Sensor installed IM1 Ex ia I Ma IECEX: Ex ia IIC T4 Ga Ex ia d IIC T4 Gb with IR Sensor installed IM1 Ex ia I Ma
EMC/RFI	EMC directive: 2004/108/EC
PERFORMANCE TESTS	LEL CSA C22.2 No. 152; ISA-12.13.01
LANGUAGES	Arabic, Chinese, Czech, Danish, Dutch, English, French, German, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, and Turkish
WARRANTY	- Four years on Liq O <sub>2</sub> sensors - Three years on CO and H <sub>2</sub> S sensors - Two years on non-consumable components and catalytic LEL sensors - One year on all other sensors, pump, battery, and other consumable parts
WIRELESS FREQUENCY	ISM license-free band. IEEE 802.15.4 Sub 1GHz Wi-Fi 802.11 b/g
WIRELESS APPROVALS	FCC Part 15, CE R&TTE, Others <sup>5</sup>
RADIO MODULE	Supports RM900A

SENSOR SPECIFICATIONS	RANGE	RESOLUTION
PID SENSORS		
VOC 9.8EV	0 to 2,000 ppm	0.1 ppm
BENZENE-SPECIFIC SNAPSHOT <sup>2</sup>	0 to 200 ppm	0.1 ppm
COMBUSTIBLE SENSORS		
CATALYTIC LEL	0 to 100% LEL	1% LEL
ELECTROCHEMICAL SENSORS		
AMMONIA (NH <sub>3</sub> )	0 to 100 ppm	1 ppm
CARBON MONOXIDE (CO)	0 to 500 ppm	1 ppm
CARBON MONOXIDE (CO), EXT. RANGE	0 to 2,000 ppm	10 ppm
CARBON MONOXIDE (CO), H <sub>2</sub> -COMP.	0 to 2,000 ppm	10 ppm
CARBON MONOXIDE (CO) + HYDROGEN SULFIDE (H <sub>2</sub> S) COMBO	0 to 500 ppm 0 to 200 ppm	1 ppm 0.1 ppm
CHLORINE (CL <sub>2</sub> )	0 to 50 ppm	0.1 ppm
CHLORINE DIOXIDE (CLO <sub>2</sub> )	0 to 1 ppm	0.03 ppm
ETHYLENE OXIDE (ETO-A)	0 to 100 ppm	0.5 ppm
ETHYLENE OXIDE (ETO-B)	0 to 10 ppm	0.1 ppm
FORMALDEHYDE (HCHO)	0 to 10 ppm	0.05 ppm
HYDROGEN CYANIDE (HCN)	0 to 50 ppm	0.5 ppm
HYDROGEN SULFIDE (H <sub>2</sub> S)	0 to 100 ppm	0.1 ppm
METHYL MERCAPTAN (CH <sub>3</sub> -SH)	0 to 10 ppm	0.1 ppm
NITRIC OXIDE (NO)	0 to 250 ppm	0.5 ppm
NITROGEN DIOXIDE (NO <sub>2</sub> )	0 to 20 ppm	0.1 ppm
OXYGEN (O <sub>2</sub> )	0 to 30% Vol.	0.1% Vol.
LIQ OXYGEN (O <sub>2</sub> )	0 to 30% Vol.	0.1% Vol.
PHOSPHINE (PH <sub>3</sub> )	0 to 20 ppm	0.1 ppm
PHOSPHINE H (PH <sub>3</sub> H)	0 to 20 ppm	0.1 ppm
SULFUR DIOXIDE (SO <sub>2</sub> )	0 to 20 ppm	0.1 ppm

<sup>1</sup> A two-gas combination sensor is required for a 6-gas configuration.

<sup>2</sup> Requires Benzene RAE-Sep Tube Cartridge

<sup>3</sup> Additional equipment and/or software licenses may be required to enable remote wireless monitoring and alarm transmission.

<sup>4</sup> RAE Systems recommends calibrating sensors on installation.

<sup>5</sup> Contact RAE Systems for country-specific wireless approvals and certificates.

Specifications are subject to change.

## ORDERING INFORMATION

- Wireless<sup>3</sup> and non-wireless configurations are available
- Refer to the Portables Pricing Guide for part numbers for monitors, consumables (RAE-Sep Tube Cartridge), accessories, sampling and calibration kits, gas, sensors, and replacement parts

## For more information

www.honeywellanalytics.com  
www.raesystems.com

## Europe, Middle East, Africa

Life Safety Distribution GmbH  
Tel: 00800 333 222 44 (Freephone number)  
Tel: +41 44 943 4380 (Alternative number)  
Middle East Tel: +971 4 450 5800 (Fixed Gas Detection)  
gasdetection@honeywell.com

## Americas

Honeywell Analytics Distribution Inc.  
Tel: +1 847 955 8200  
Toll free: +1 800 538 0363  
detectgas@honeywell.com  
Honeywell RAE Systems  
Phone: +1 408 952 8200  
Toll Free: +1 888 723 4800

## Asia Pacific

Honeywell Analytics Asia Pacific  
Tel: +82 (0) 2 6909 0300  
India Tel: +91 124 4752700  
China Tel: +86 10 5885 8788-3000  
analytics.ap@honeywell.com

## Technical Services

EMEA: HAexpert@honeywell.com  
US: ha.us.service@honeywell.com  
AP: ha.ap.service@honeywell.com

Datasheet\_MultiRAE Benzene\_DS-1098-11\_US-EN  
04/18 ©2018 Honeywell International Inc.

**Honeywell**